



TIMELESS



Characteristics

Metallic textile engraving with a broad color palette designed for a stand out elegance in spaces like hotels, offices or others

Technical properties

|                     |            |                     |
|---------------------|------------|---------------------|
| Width               | 140        | cm                  |
| Roll length         | 25         | meters              |
| Weight              | 670        | gr/m2               |
| Composition         | 77%        | Biodegradable PVC   |
|                     | 5%         | Water based PU      |
|                     | 18%        | Recycled PES fabric |
| Biodegradability    | ASTM       | D 5511-11           |
| Toxicity            | ASTM       | E 1963              |
| Abrasion resistance | ASTM       | D4157 -100.000 dr   |
| UV resistance       | AATCC      | 16.3 - 40hrs        |
| Antimicrobial       | ASTM       | G21 - 96            |
| Flammability        | California | Bulletin 117-2013,  |
|                     | NFPA 260 , | ASTM E662           |

Care

Please clean the material regularly with warm soapy water. Pollution by oil, fat and ink must be removed immediatly. Do not use solvents. Only use alcohol when necessary

Special note

When manufacturing, if necessary, use only water based adhesives and avoid mixing different lots for the same task, because little color variation could occur. Our recommendations are based on our experience, but they do not release the purchaser from checking our product for the intended use

Características

Grabado textil metalizado de amplia paleta de colores, desarrollado para resaltar elegancia en espacios tales como en hotel, oficina u otros

Propiedades técnicas

|                      |            |                       |
|----------------------|------------|-----------------------|
| Ancho                | 140        | cm                    |
| Largo rollo          | 25         | metros                |
| Peso                 | 670        | gr/m2                 |
| Composición          | 77%        | PVC biodegradable     |
|                      | 5%         | PU base agua          |
|                      | 18%        | Tela de PES reciclado |
| Biodegradabilidad    | ASTM       | D 5511-11             |
| Toxicidad            | ASTM       | E 1963                |
| Abrasión             | ASTM       | D4157 -100.000 dr     |
| Resistencia UV       | AATCC      | 16.3 - 40hrs          |
| Antimicrobial        | ASTM       | G21 - 96              |
| Retardancia al fuego | California | Bulletin 117-2013,    |
|                      | NFPA 260 , | ASTM E662             |

Cuidados

Limpiar el material regularmente con agua jabonosa tibia. Manchas de aceite, grasa o tinta deben ser removidas inmediatamente. No utilizar solventes. En casos extremos utilizar alcohol

Nota especial

En la fabricación del mueble, cuando sea necesario, utilizar sólo adhesivos en base a agua y evitar mezclar partidas en una misma tarea, ya que pueden existir pequeñas variaciones de color. Nuestras recomendaciones están basadas en nuestra experiencia, pero no liberan al comprador de chequear los productos para la aplicación particular

